

Информация о заказчике и сроках поставки (обязательно для заполнения)

Заказчик, контактное лицо, E-mail, тел.

Адрес доставки

Высота (R) ММ

Кол-во остановок

Lower floor service height (HO) ММ

Self-supporting structure SI NO

Источник питания (±5%)

- 230V 3~ 50 hz
 400V 3~ 50 hz
 230V 1~ 50 hz
 Other

Грузоподъёмность

- 50 Kg
 100 Kg

Тип привода

- Hydraulic
 (Maximum travel 8000 mm)
 Electric
 (Maximum travel 35000 mm)

Floor numbering

Lift-Car characteristics

Car layout №

- 1 2 3 4 5 6 7

№ Shelves in car

Car finishing

- Baked enamel finish
 Stainless steel
 Stainless steel AISI 316

Car Options

- Car door included
 Shelf heating

Door characteristics

Landing door type

- Bi-parting
 Swing-hinged
 PF-60 Bi-parting
 Automatic Bi-parting

Landing door finishing

- Baked enamel finish
 Stainless steel
 Stainless steel AISI 316

Landing door configuration

Quantities

Hand

- | | Quantities | Hand |
|--------------|----------------------|----------------------|
| Doors pos. 1 | <input type="text"/> | <input type="text"/> |
| Doors pos. 2 | <input type="text"/> | <input type="text"/> |
| Doors pos. 3 | <input type="text"/> | <input type="text"/> |

Options

Mechanical options

- Machine room trap door
 Backed enamel finish
 Stainless steel
 Car and door type "duplex"

Hydraulic options

- Rupture valve
 Flexible pipe, lenght mm
 (for power unit outside the shaft)

Electrical control options

- Key to disable landing operating panel

Packing options

- Accessories and doors in wooden box

Remarks

Dimensions

